THE ONE BOX SOLUTION FOR CYLINDRICAL AND MORTISE LOCKS





Electric Characteristics

<u>Voltage</u>	Current/Amps	<u>Ohms</u>	<u>Duty</u>	<u>Sound</u>
12DC	0.240	50	Intm./Cont.	Silent
24DC	0.114	210	Intm./Cont.	Silent
12AC @ 60	hz 0.210	50	Intm.	Buzz
16AC @ 601	hz 0.280	50	Intm.	Buzz
24AC @ 601	nz 0.420	50	Intm.	Buzz

Power Matters

Low Current Draw .240 Amp at 12DC makes it very PoE Friendly



12 & 24DC :: 12 through 24AC All the low voltage flexibility you need.

In The Box:

- The four faceplates
- 2 Premium stainless steel trim skirts
- Standard and Torx[®] screws
- Latch shims
- Plug-in style wire connectors
- Sealed crimp connectors



4100-32D (Satin Stainless Steel – BHMA630)

- The following finishes are:
- 4100-32 (Polished Stainless Steel BHMA629)
- **4100-US3** (Bright Brass BHMA605)

The following finishes are:

- 4100-US4 (Satin Brass BHMA606)
- 4100-US10 (Satin Bronze BHMA612)
- 4100-US10B (Dark Bronze BHMA613)

For Fail-safe action (locks with power) add "RS" to the item number. EX: 4100RS-32D

Faceplates, strike body, mounting screws, and trim skirts all match the finish.

www.trineonline.com