



## ACCESSORIES



### 100

#### Set Screw Set

- 1/8" x 10-32 set screws (quantity 300)
- 3/16" x 10-32 set screws (quantity 300)
- 3/32" hex key
- Hand tap "T" wrench
- 10-32 tap
- #21 drill bit
- This set converts removable pin hinges to non-removable pin (set screw in barrel) hinges as required



### 263

#### Sleeve Bolt

- Aluminum
- 9/16" (14 mm) head sex nut with 1/4" - 20 internal thread
- Knurled shoulder prevents bolt from turning
- Drill a 3/8" (9.5 mm) hole and insert the sex bolt
- Available in US2C finish only (compatible with US26D, US28, or US32D)
- For use in securing push bars, exposed door closers and other fixtures to doors 1-3/4" (45 mm) thick or greater



### 265

#### Molly Jack Nut (8S JN)

- Aluminum
- For use with the Hager reinforcing pivot hinges (250 Series)
- Easily installed by drilling a 7/16" (11.1 mm) pilot hole and following the instructions provided with each product
- For use in properly anchoring various products to hollow metal frames 3/16" - 3/8" (4.8 mm - 9.5 mm) thick



### 305

#### Hinge Reinforcement Plate

- Steel
- For metal frames
- Four (4) holes

Hinge Size		Width		Total Length	
Inches	mm	Inches	mm	Inches	mm
4-1/2	114	1.5	38	10	254
Offset		Gauge of Metal		Tapped for Screw	
0.074		0.154		12-24	



### 417

#### Back Plate

- Steel
- For wood doors
- For full or half surface hinges

Length		Width		Gauge of Metal
Inches	mm	Inches	mm	
4-5/8	117	1-13/16	46	0.074
5	127	2-1/8	54	0.097
Number of Holes		Machine Screw Size		
3		1/4 x 20		
4		1/4 x 20		