

11B Specifications

Case – Machined from solid extruded brass
Standard Finish – 626 satin chromium plated
Width – 1-5/8"
Length – 2-1/16"
Thickness – 25/32"
Shackle: The shackle locks at both heel and toe. The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.
Material – Brass or stainless steel
Diameter – 1/4"
Width or opening – 7/8"
ASTM F883 – Meets Grade 3 with stainless steel shackle
ASTM 5883 – Meets Grade 6 for option E. (Corrosion resistance).



11B Padlock



11B72

11B722

11B772

11B782

How To Order – 11B

Series	Core Housing	Shackle Height	Function Code	Chain Option	Special Stamp No.	Options
11B – brass 1/4" diameter	7 – 7 pin housing accepts all BEST® cores	2 Steel 2 – 3/4" 22 – 1-1/2" 72 – 2" 82 – 4" Brass 0 – 3/4" 20 – 1-1/2" 70 – 2" 80 – 4"	T – key retained L – non-key retained	M – case drilled for clevis only M1* – bronze chain (available for brass padlocks only) M5* – galvanized steel chain	Blank – BEST® logo PS1010 – safety first Specify padlock stamp number or describe stamp. Price for special stamps on request	F3 – rangible shackle (11B720 only) 606 – satin brass ZZ – double lockout
					page 8	page 8