



Home About Us Products Tech Support Sales Reps  
Where to Buy News/Media Contact

Select a Search Term

## Trines Adjustable 2000 Series Electric Strikes

### Light Commercial Strikes

[00 Series](#)

[01 Series](#)

[2000 Series](#)

[1000 Series](#)

#### 2000 Series Features:

- Allows adjustment for wider latch bolts & poorly aligned doors & locksets.
- **1/8" Horizontal Latch Adjustment.**
- Releases Under Slight Door Pre-Load.
- 500,000 Life Cycles -- Holding Force - 900 lbs.
- Solid Cast Latch - Chrome Plated.
- Non Handed Operation.
- Screw Terminals - Quick Connection.



#### 2000 Series Electrical Characteristics:

Voltage	Current/Amps	Ohms ( $\Omega$ )	Sound	Duty
6-14VAC	0.44 - 1.10	8.5	Buzz	Intermittent
6-14VDC	0.70 - 1.60	8.5	Silent	Continuous
16-24VAC	0.22 - 0.33	50.0	Buzz	Intermittent
16-24VDC	0.32 - 0.47	50.0	Silent	Continuous
12VDC	0.20 - 0.33	60.0	Silent	Continuous
24VDC	0.11 - 0.47	120.0	Silent	Continuous

#### 2001

For use in new or replacement wood or metal jamb installations with locksets having up to 5/8" th 1/8" door gap.

*Face Plate 5-7/8" x 1-1/4" -- Narrow Style Face Plate -- Mortise Backset 1-9/16" -- Cavity Depth 9/16" -- Width 5/8" -- Cavity Height 1-11/16"*

**Available Finishes:** 2001 (Brass Powder Coated) -- 2001C (Satin Chrome or - BHMA652)

**Downloadable content:**

- [2001 Dimensions \(PDF\)](#)

**2002**

For use in new or replacement aluminum or hollow metal jamb installations. Auxiliary lever ramps locksets containing dead-locking levers. Use with latch bolts having up to 5/8" throw, Based on 1.


*Face Plate 7-15/16" x 1-7/16" -- Auxiliary Ramp Height 2-7/8" -- Mortise Backset 1-9/16" -- Cavity Cavity Width 5/8" -- Cavity Height 1-11/16"*

**Available Finishes:** 2002 (Aluminum Powder Coated) -- 2002DB (Dark Bronze Powder Coated)  
**Options:** RS (Fail Safe) -- on DC only -- add "RS" to model #

**Downloadable content:**

- [2002 Dimensions \(PDF\)](#)

**2002WR**

For use in new or replacement aluminum or hollow metal jamb installations. Auxiliary lever ramps for use with locksets containing dead-locking levers. Use with locksets having up to 5/8" throw, based on 1/8" door gap. 

*Steel Face Plate 7-15/16" x 1-7/16" -- Auxiliary Ramp Height 3-3/8" -- Mortise Backset 1-9/16" -- Cavity Depth 9/16" -- Cavity Width 5/8" Cavity Height 1-11/16"*

**Available Finishes:** 2002WR (Aluminum Powder Coated) -- 2002WRDB (Dark Bronze Powder Coated)

**Options:** RS (Fail Safe) -- on DC only -- add "RS" to model #

**Downloadable content:**

- [2002WR Dimensions \(PDF\)](#)

**2007**

For use in new or replacement installations in metal jambs. Fits a standard 4-7/8" ANSI prep with modification. Use with locksets having up to 5/8" throw, based on 1/8" door gap.

*Steel Face Plate 4-7/8" x 1-1/4" -- Narrow Style Face Plate -- Mortise Backset 1-9/16" -- Cavity D*