

410 & 420 Series Exit Switches

The illuminated switch button is two inches square for easy activation and is visually conspicuous. The high impact resistant material stands up to abuse. The "PUSH TO EXIT" sign complies with NFPA requirements. The 422A is designed for access and egress applications for the ADA applications.



410



420



420A



FEATURES

- Green or Red or ADA Blue Illuminated Switch Button
- Dull Stainless Steel Finish
- Push-to-Exit or Handicap Sign
- Green and Red Lens



SPECIFICATIONS

Switch Contact	SPDT/DPDT, 5 Amp @ 30VDC Resistive
Timer Contacts	DPDT 2 Amp @ 12/24VDC
Wire Leads	6", 20 Gauge
1 Gang	2 7/8" x 4 1/2" x 20 Ga.
Narrow	1 3/4" x 4 1/2" x 20 Ga.
Weight	0.4 lbs



MODELS

410 NARROW SERIES 1-3/4" X 1" EXIT SWITCH

412N	Momentary SPDT	PUSH TO EXIT
413N	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact	UL 294 PUSH TO EXIT
413PN	Integrated Pneumatic Timer, adj. 1-180 Sec. 12/24VDC, DPST 3 Amp Contact, Screw Terminals	PUSH TO EXIT
414N	Momentary DPDT	PUSH TO EXIT
415N	AA (On/Off) DPDT	NONE

NOTE: AA Models Are Not Illuminated

420 1 GANG SERIES 2" EXIT SWITCH

422	Momentary SPDT	PUSH TO EXIT
422A	Momentary SPDT, ADA Blue	SYMBOL
423	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact	UL 294 PUSH TO EXIT
423P	Integrated Pneumatic Timer, adj. 1-180 sec, 12/24VDC, DPST 3 Amp Contact, Screw Terminals	PUSH TO EXIT
423A	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact, ADA Blue Illuminated	SYMBOL
424	Momentary DPDT	PUSH TO EXIT
425	AA (On/Off) DPDT	NONE

NOTE: AA Models Are Not Illuminated



 HOW TO ORDER

1| SPECIFY MODEL

410 NARROW SERIES 1-3/4" X 1" EXIT SWITCH

412N	Momentary SPDT	PUSH TO EXIT
413N	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact, UL 294 Listed	PUSH TO EXIT
413PN	Integrated Pneumatic Timer, adj. 1-180 sec, 12/24VDC, DPST 3 Amp Contact, Screw Terminals	PUSH TO EXIT
414N	Momentary DPDT	PUSH TO EXIT
415N	AA (On/Off) DPDT	NONE

NOTE: AA Models Are Not Illuminated

420 1 GANG SERIES 2" EXIT SWITCH

422	Momentary SPDT	PUSH TO EXIT
422A	Momentary SPDT, ADA Blue	 SYMBOL
423	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact, UL 294 Listed	PUSH TO EXIT
423P	Integrated Pneumatic Timer, adj. 1-180 sec, 12/24VDC, DPST 3 Amp Contact, Screw Terminals	PUSH TO EXIT
423A	Integrated Electronic Timer, adj. 1-60 sec, 12/24VDC, 2A DPDT Contact, ADA Blue Illuminated	 SYMBOL
424	Momentary DPDT	PUSH TO EXIT
425	AA (On/Off) DPDT	NONE

NOTE: AA Models Are Not Illuminated

2| SPECIFY FINISHES

U 630 Stainless Steel - STANDARD	D 606 Dull Brass
C 605 Bright Brass	P 625 Bright Chrome
H 613 Oil Rubbed Bronze	

3| SPECIFY LED OPTIONS

L1G 1 Green LED	LT Tri-color LED - Red, Green, Amber
L1R 1 Red LED	L2 1 Red,1 Green LED