



## 4700 SERIES - STANDARD DUTY RIM DEVICE

### WARRANTY

Five-year warranty

### FEATURES

Certification:	Meets life safety codes and fire-safety requirements. See charts on page 44 for details and options.
Covers:	Cast brass, bronze, stainless steel, zinc
Cover Tube:	Painted steel, plated steel, stainless steel
Dogging:	Hex dogging feature standard on non-fire labeled doors
End Caps:	Painted steel, plated steel, stainless steel
Fasteners:	<ul style="list-style-type: none"> <li>• Wood and machine screws</li> <li>• Thru-bolts supplied standard</li> </ul>
Latchbolt:	3/4" (19 mm) throw, pullman type with automatic dead-latching, stainless steel
Strikes:	<ul style="list-style-type: none"> <li>• Stainless steel with stainless steel pin and roller - included standard with panic and fire-rated devices</li> <li>• Surface applied to frame with slotted holes for easy adjustment</li> <li>• Optional double door strike for use with surface vertical rod and rim devices</li> </ul>



### SPECIFICATIONS

Door Thickness:	1-3/4" (44 mm) - Standard
Door Width:	<ul style="list-style-type: none"> <li>• 36" (914 mm) field sizeable to 30" (762 mm) door</li> <li>• 48" (1219 mm) field sizeable to 36" (914 mm) door</li> </ul>
Projection:	<ul style="list-style-type: none"> <li>• 2-7/16" (62 mm) in undogged position</li> <li>• 1-3/16" (30 mm) in dogged position</li> </ul>
Stile Width:	<ul style="list-style-type: none"> <li>• 4-1/2" (114 mm) - minimum stile width required for single door and 5/8" (16 mm) stop</li> <li>• 4-1/2" (114 mm) - minimum stile width required for double door x surface vertical rod device with double door strike</li> <li>• 3-3/4" (95 mm) - minimum stile width required for double door x mullion x 4920 strike</li> <li>• 5" (127 mm) - minimum stile width required for double doors with 2" (51 mm) mullion</li> <li>• All stile widths are measured from door edge</li> </ul>
Notes:	<ul style="list-style-type: none"> <li>• Cylinders sold separately</li> <li>• Escutcheon and thumbpiece pull plate trim is handed</li> <li>• Apollo knob is not ADA compliant</li> <li>• Recommended for use on appropriately reinforced doors</li> </ul>

### TRIM

- 4700 Series escutcheon trim for rim device is available with a variety of lever options (p. 51)
- 4700 Series key-in-trim is available with a variety of lever options plus a knob option (p. 53)
- Pull plate trim
- Raised lip pull
- Rim cylinder x optional pull

### FINISHES

US3, US32D, ALM, DBZ

