



(7)

Precision 5000 Series Exit Devices by BEST

Accessories

Cylinder Dogging



Available for all Precision Series Devices except for Fire Exit Hardware.

Cylinder Dogging provides the ability to lock down the touchbar with a key cylinder so the door can be used in the push pull mode. To order, specify suffix "CD" (e.g. 5100CD). Requires the use of a 1-1/4" mortise cylinder, not furnished standard. Specify when required.

Less Dogging

Available for all Precision Series Devices except Fire Exit.




Cylinder Dogging Kit


To convert from hex key dogging to cylinder dogging in the field, a cylinder dogging kit is available. The kit consists of a channel filler, blocking ring, cylinder locator and lock nut. Requires the use of a 1-1/4" mortise cylinder, not furnished standard. Specify when required.

To order specify: RCDK-3, for up to 3'-0" and RCDK-4 for devices up to 4'-0".

Strikes









2-3/8"

S460 Bottom Strike

For Vertical Rod Devices,

Black Powder Coated Steel.

Surface or Concealed.

1-5/8"



a Mullion, Black Powder Coated

Investment Cast Stainless Steel.

Miscellaneous



End Cap REC999 For Hinge Stile end of all Precision Devices.



Mounting Bracket MB305 For Hinge Stile end of all Precision Devices.



Rod Guide RRG123 For surface vertical rod devices.

DK220 - 7/32" standard hex.



Top Rod - 5200 Series. Three stock lengths available for 7'-0", 8'-0, and 10'-0" high doors.

RTŘ1860 – For 7'-0" doors, rod is 37-3/8" long. For 8'-0" doors, rod is 49-3/8" long. RTR1861 RTR1863 - For 10'-0" doors, rod is 73-3/8" long.

For doors of lesser heights rods are cut on job. Specify finish 689 or 695. Includes Rod Pin

