5000/5200 Series Faceplate Options

OPERATION	After releasing the latchbolt, the keeper returns to the locked position.	
4-7/8" × 1-1/4" [123.8mm × 31.75mm] Square corners and flat faceplate	501 Option For use with: Cylindrical locksets in ANSI metal jambs ANSI/BHMA Numbers: E09321, E09322, E09323	
4-7/8" × 1-1/4" [123.8mm × 31.75mm] Radius corners and flat faceplate	501A Option For use with: Cylindrical locksets or spring latch in aluminum frames. Includes universal mounting tabs. ANSI/BHMA Numbers: E09321, E09322, E09323	
7-15/16" × 1-7/16" [201.6mm × 36.5mm] Radius corners and flat faceplate	502 Option For use with: Cylindrical locksets or spring latch in aluminum frames. Includes universal mounting tabs. ANSI/BHMA Numbers: E09321, E09322, E09323	
6-7/8" × 1-1/4" [174.6mm × 31.75mm] Radius corners and flat faceplate	503 For use with: Cylindrical locksets or spring latch in aluminum frames. Includes universal mounting tabs. ANSI/BHMA Numbers: E09321, E09322, E09323	
10" × 1-3/8" [254mm × 34.9mm] Radius corners and flat faceplate	504 For use with: Cylindrical locksets. Four-point mounting for wood installations ANSI/BHMA Numbers: E09321, E09322, E09323	

[&]quot;For use with" information is offered as a recommendation only. Reference should be made to the lockset manufacturer for proper installation instructions necessary to meet compatibility requirements.



ASSA ABLOY