


A	Hinges & pivots
B46	Pulls & plates
C	Flush bolts & coordinators
D	Latches, catches & bolts
E	Stops
F	Exterior hardware
G	Miscellaneous hardware



8311 Pull plate

Certifications

- Meets ANSI A156.06

Mounting

- 1/4-20 mounting hardware
- Specify door thickness. Standard mounting hardware for door thickness of 1-1/2" to 1-3/4" unless otherwise specified. Optional package available for 2" and 2-1/4" thick doors.
- Comes standard with through bolt screws and decorative washers.
- Optional mounting hardware available (see general information section for details) F, G
- Mounting hardware for other door thicknesses are available as engineering special, consult customer service.
- Standard mounting package for plate
 - #6 X 5/8 oval head screws
- Optional TEK/TORX package
 - #6 X 5/8 Self-drilling, Self-tapping screws and
 - #6 X 5/8 Torx screws
- Plate prepped with 2 pull mounting holes spaced at 5-1/4" center to center

Widths and heights

- 3-1/2" X 15"
- 4" X 16"
- 6" X 16"

Pull center to center

- 5-1/4"

Material substrate

- Made from aluminum, brass, or stainless steel (300 Series)

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
626-AM	Satin chrome anti-microbial	Brass	US26D-AM
628	Clear anodized	Aluminum	US28
630	Satin stainless	Stainless steel	US32D
630-AM	Satin stainless anti-microbial	Stainless steel	US32D-AM
631	Matte black	Stainless steel	BLK
643e/716	Aged bronze	Stainless steel	643e/716

Note: For other colors, consult factory.

Additional information

- Specify PR when ordering a set of pulls for back to back mounting
- Custom widths, heights, and special cut-outs are available as engineering special, consult customer service.