Simplex[®] 9600 Series

0



- Mechanical Pushbutton Lock
- Single Access Code
- Deadbolt/Spring Latch
- Thumbturn

Features

| Access Control: | Mechanical pushbutton lock eliminates problems and costs associated with |
|--------------------------|---|
| | issuing, controlling, and collecting keys and cards. Uses same combination system |
| | as our other pushbutton access controls and are specifically designed |
| | for cabinet doors, desk drawers, and similar applications. Ideal for use in many |
| | locations: medicine chests, liquor cabinets, gun boxes, courier pick-up boxes, |
| | home entertainment units, cleaning supply cabinets, tool chests, private files, |
| | audio-visual cabinets, and petty cash drawers. |
| No Battery: | Fully mechanical lock eliminates the material and labor expense of battery replacements |
| Locking Device Options: | Flat deadbolt |
| | Round deadbolt |
| | Round spring latch bolt |
| Number of Codes: | Single access code—one easy-to-manage code for all users |
| Programming: | Lock is easily programmed via keypad without removing lock from the door |
| Handing: | Non-handed |
| Operation Modes: | Single credential access |
| Economical: | A cost effective access control solution |
| Key Override (Optional): | Select models |
| Mechanical Features | |
| Construction: | All metal cast face plate; force-resistant, protected exterior knob |
| Numeric Keypad | Vandal resistant solid metal pushbuttons |

| Numeric Keypad: | Vandal resistant, solid metal pushbuttons |
|-----------------|--|
| Handing: | Non-handed |
| Finishes: | Bright Brass 03 (605), Satin Brass 04 (606), and Satin Chrome 26D (626); |
| | black trim plate (optional) |
| Weight: | 1 lb. (0.5 kg) |
| Bolt: | End-throw/cross-throw deadbolt (must be manually relocked) |
| | End-throw/cross-throw spring latch (with automatic relock) |
| | Double-throw bolt (sheet metal, end throw only) |



| Door Thickness: | Wood doors: 5/" (16 mm) to 1/" (22 mm) |
|-----------------|--|
| | Sheet metal applications: 14 to 20 gauge |
| Installation: | Horizontal or vertical. Two-step mortise installation using router or 51/2" |
| | (140 mm) x 1" (25 mm) slot with trim plate (for wood applications). |
| | Punched slot or series of χ_6 " (11 mm) drilled holes (for metal applications). |

| Warranty | |
|-----------|-----------------|
| Warranty: | 1-year warranty |

Cabinet Lock

Escutcheon Plate







Exterior

Side View

Exterior with Trim Plate