

ADVANTEX® 10 SERIES (WIDE RIM)

RATING

For no rating, leave blank

H = Hurricane Rated

F = Fire Rated (Less/No Dogging Only)

FH = Hurricane and Fire Rated

KNURLING

For no knurling, leave blank

KN = Knurled (lever trim only)

SERIES TYPE

10 = Rim device, wide stile

10xW = Weatherized Rim device, wide stile (non-electrified)

OUTSIDE TRIM / DEVICE FINISH

605 = Polished brass (PVD)

606 = Brushed brass (PVD)

611 = Polished bronze (PVD)

612 = Brushed bronze (PVD)

613 = Oil rubbed bronze

625 = Polished chrome

626 = Brushed chrome (std. on lever trims)

629 = Polished stainless steel

630 = Brushed stainless steel (std. on pull trims & device)

693 = Black, powder coated

695 = Dark bronze, powder coated

DOGGING FUNCTION

LD = Less/No dogging

HD = Hex key dogging

CD = Cylinder key dogging

PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

MC65 = Mortise Cylinder(s) 6pin/Keyed 5

IC7 = Mortise Cylinder(s) SFIC housing

IK7 = Mortise Cylinder(s) InstaKey housing

RC65 = Rim Cylinder(s) 6pin/Keyed 5

IC7R = Rim Cylinder(s) SFIC housing

IK7R = Rim Cylinder(s) InstaKey housing

ENDCAP

EC1 = Ramped endcap*

EC2 = Flush endcap (std. on

all 628/693/695 finishes)

FLEX CONDUIT

For no flex conduit, leave blank

FC = End Cap with Flex Conduit

FASTENERS

For standard machine, wood & self-drilling screws, leave blank

SN1 = Sex Nuts/ Throughbolts (Hurricane rated hardware includes sex nuts for latch bolt)

STRIKES

98 = Semi-Mortise

99 = Surface*

94 = Double-Door (least secure)

ANTIMICROBIAL

For no coating, leave blank

AM = Antimicrobial Coating

KEYSTOP

For no keystone, leave blank

KS = Key Stop (Available with EA, EBxW, EE, EExER, EI functions)

DOOR WIDTH

24" wide door

30" wide door

36" wide door (3")*

48" wide door (4")

SILENCER

For standard pushpad, leave blank

SLR = Silent Latch & Pushpad

OUTSIDE TRIM FUNCTION

For no outside trim, leave blank

01C = Exit only, blank plate

01W = Exit only, wide blank plate - long

02C = Dummy pull trim

02Z = Inactive Vandal pull handle (handed)

03C = Key retracts latch; pull trim

03Z = Key retracts latch; Vandal pull handle (handed)

03W = Key retracts latch; wide plate - long

03WS = Key retracts latch; plate - short

01D = Blank escutcheon

02D = Dummy lever trim

08D = Active lever, key locks / unlocks lever; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (classroom)

09D = Lever trim active by key, locked when key removed; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (storeroom)

10D = Double cylinder; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (passage)

14D = Active lever, no key cylinder; Wide lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (passage)

CBK = Cylinder bracket kit, 03 only, plate & pull handle by others required

EU = Electric Unlock Trim (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify 12VDC. For Fail Safe specify FSA

Fire-rated trims must be fail safe (FSA)

**Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only. See catalog pages for more information.

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Standard

Select Arming Time and Auto Rearm

EA = Hardwired Elec. Alarm

EAXEX = Exit Alarm with Request To Exit (Signal) Switch

EAXEXV = Exit Alarm with Request To Exit (3Amp Current) Switch

ED = Elec. Dogging

EX = Request To Exit (Signal) Switch

EXV = Request To Exit (3Amp Current) Switch

EI = Elec. Integration (logic controller required)

ES = Elec. Switching (dead latch & OKC switches)

Delayed Egress

Select Arming Delay, Delayed Egress Time and Silent Arming

EE = Delayed Egress

Power Supply for Delayed Egress

Comes standard with 90-800 power supply

Single = (1) 90-800 w/o bat backup

Pair = (1) 90-800 w/o bat backup

Weatherized Alarms

Select Arming Time and Auto Rearm

EBxW = Elec. Battery Operated Exit Alarm Weatherized

EBxEXxW = Elec. Battery Operated Exit Alarm Weatherized with Request To Exit (Signal) Switch

EBxEXVxW = Elec. Battery Operated Exit Alarm Weatherized with Request To Exit (3Amp Current) Switch

Latch Retraction

ER = Elec. Latch Retraction (silencer standard)

ERxW = Elec. Latch Retraction Weatherized (silencer standard)

Power Supply / Controller for Latch Retraction Only (ER & ERxW)

Order/Sold Separately

Single = 81-800

Pair = 82-800

2 Independent Singles = 83-800

Weatherized Others

ERxW = Elec. Latch Retraction Weatherized (silencer standard)

EXxW = Request To Exit (Signal) Switch Weatherized

EXVxW = Request To Exit (3Amp Current) Switch Weatherized

WDE = Weatherized Delayed Egress (see EasyKits)

Delayed Egress/Latch Retraction

EExER = Delayed Egress with Elec. Latch Retraction (silencer standard)

EExERxULC = Delayed Egress with Elec. Latch Retraction (silencer standard) UL Canada

Required Power Supply / Controller for Delayed Egress with Latch Retraction (EExER)

Order/Sold Separately

Single EExER = 84-800

Pair of EExER = 85-800

One EExER and One EE = 85-800xEE

One EExER and One ER = 85-800xER

NOTE: * = default/standard

Also see online version at detex.com/hto

November 30, 2016