

ADVANTEX® 60/61/62/63 SERIES (NARROW CONCEALED VERTICAL ROD)

RATING

For no rating, leave blank

F = Fire Rated (Less/No Dogging Only)

KNURLING
For no knurling, leave blank
KN = Knurled (lever trim only)

SERIES TYPE

- 60 = CVR/EC2, narrow stile, aluminum door
- 61 = CVR/EC2, top rod only, narrow stile, aluminum door
- 62 = CVR, narrow stile, hollow metal door
- 63 = CVR, top rod only, narrow stile, hollow metal door

OUTSIDE TRIM / DEVICE FINISH

605 = Polished brass (PVD)
606 = Brushed brass (PVD)
611 = Polished bronze (PVD)
612 = Brushed bronze (PVD)
613 = Oil rubbed bronze
625 = Polished chrome
626 = Brushed chrome (std. on lever trims)
629 = Polished stainless steel
630 = Brushed stainless steel (std. on pull trims & device)
693 = Black, powder coated
695 = Dark bronze, powder coated

DOGGING FUNCTION

LD = Less/No dogging
HD = Hex key dogging
CD = Cylinder key dogging

PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

MC65 = Mortise Cylinder(s) 6pin/Keyed 5
IC7 = Mortise Cylinder(s) SFIC housing
IK7 = Mortise Cylinder(s) InstaKey housing
RC65 = Rim Cylinder(s) 6pin/Keyed 5
IC7R = Rim Cylinder(s) SFIC housing
IK7R = Rim Cylinder(s) InstaKey housing

ENDCAP

EC1 = Ramped endcap*
EC2 = Flush endcap (std. on all 628/693/695 finishes)

ANTIMICROBIAL

For no coating, leave blank
AM = Antimicrobial Coating

FLEX CONDUIT

For no flex conduit, leave blank
FC = End Cap with Flex Conduit

FASTENERS

For standard machine, wood & self-drilling screws, leave blank
SN1 = Sex Nuts/Throughbolts

DOOR HEIGHT/CVR HEIGHT

For 80-96" door heights, leave blank
" " - 80" - 96" high door
120 - 97" - 120" high door

STRIKES

95T = CVR, top strike
95B = CVR, bottom strike

KEYSTOP

For no keystone, leave blank
KS = Key Stop (Available with EA, EE, EEXER, EI functions)

DOOR WIDTH

24" wide door
30" wide door
36" wide door (3')*
48" wide door (4')

SILENCER

For standard pushpad, leave blank
SLR = Silent Latch & Pushpad

OUTSIDE TRIM FUNCTION

For no outside trim, leave blank

02WP = Dummy wire pull handle
01CNV = CVR, narrow blank plate
02CNV = CVR, Dummy pull handle
03CNV = CVR, Key retracts latch; Narrow pull handle
03R = CVR, Key retracts latch; Cylinder escutcheon
02DNV = CVR, Dummy narrow lever handle (handed) (S, T or U lever)
08DNV = CVR, Active lever, key locks / unlocks lever; Narrow lever handle (handed) (S, T or U lever) (classroom)
09DNV = CVR, Lever trim active by key, locked when key removed; Narrow lever handle (handed) (S, T or U lever) (storeroom)
14DNV = CVR, Active lever, no key cylinder; Narrow lever handle (handed) (S, T or U lever) (passage)

DOOR HANDING

RHR = Right hand reverse*
LHR = Left hand reverse

SWITCHING

For no switching, leave blank
LX = Latch Bolt Signal Switch
LXV = Latch Bolt 3Amp Current Switch

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Standard

Select Arming Time and Auto Rearm

EA = Hardwired Elec. Alarm
EAXEX = Exit Alarm with Request To Exit (Signal) Switch
EAXEXV = Exit Alarm with Request To Exit (3Amp Current) Switch
ED = Elec. Dogging
EX = Request To Exit (Signal) Switch
EXV = Request To Exit (3Amp Current) Switch

Delayed Egress

Select Arming Delay, Delayed Egress Time and Silent Arming
EE = Delayed Egress

Power Supply for Delayed Egress

Comes standard with 90-800 power supply
Single = (1) 90-800 w/o bat backup
Pair = (1) 90-800 w/o bat backup

Latch Retraction

ER = Elec. Latch Retraction (silencer standard)
ERxW = Elec. Latch Retraction Weatherized (silencer standard)

Power Supply / Controller for Latch Retraction Only (ER & ERxW)

Order/Sold Separately
Single = 81-800
Pair = 82-800
2 Independent Singles = 83-800

Weatherized Others

ERxW = Elec. Latch Retraction Weatherized (silencer standard)
EXxW = Request To Exit (Signal) Switch Weatherized
EXVxW = Request To Exit (3Amp Current) Switch Weatherized
WDE = Weatherized Delayed Egress (see EasyKits)

Delayed Egress/Latch Retraction

EEXER = Delayed Egress with Elec. Latch Retraction (silencer standard)
EEXERxULC = Delayed Egress with Elec. Latch Retraction (silencer standard) UL Canada

Required Power Supply/Controller for Delayed Egress with Latch Retraction (EEXER)

Order/Sold Separately
Single EEXER = 84-800
Pair of EEXER = 85-800
One EEXER and One EE = 85-800xEE
One EEXER and One ER = 85-800xER

Fire-rated trims must be fail safe (FSA)

**Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only. See catalog pages for more information.

NOTE: * = default/standard

Also see online version at detex.com/hto

July 26, 2016