



SCHLAGE

Portable
security and
cabinet locks



Cabinet locks with cylinder

Cabinet deadbolt locks



CL100PB

Cylinder formats:

CL100PB - Conventional format

Interchangeable Core formats:

CL777R - Full Size IC (FSIC)
CL721G - Small Format IC (SFIC)

Rekeying: Release mechanism allows Conventional cylinder replacement. Interchangeable cores replaced using control key

Certifications: ANSI 156.11 - Conventional Grade 1; FSIC and SFIC Grade 2

Body: Die cast zinc

Bolt: Steel $15/16$ " projection; $3/4$ " SFIC

Door thickness: $7/8$ " to $13/8$ "

Barrel diameter: $11/8$ "

Finishes: Conventional and FSIC formats - 605 and 626; SFIC format - 626 only

Drawer deadbolt locks



CL771G

Cylinder formats:

CL200PB - Conventional format

Interchangeable Core formats:

CL888R - Full Size IC (FSIC)
CL771G - Small Format IC (SFIC)

Rekeying: Release mechanism allows Conventional cylinder replacement. Interchangeable cores replaced using control key

Certifications: ANSI 156.11 - Conventional Grade 1; FSIC and SFIC Grade 2

Body: Die cast zinc

Bolt: Steel $3/4$ " projection

Door thickness: $7/8$ " to $13/8$ "

Barrel diameter: $11/8$ "

Finishes: Conventional and FSIC formats - 605 and 626; SFIC format - 626 only

Rim deadbolt lock



CL775G

Interchangeable Core format:

CL775G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc cylinder housing, stamped steel back plate and steel case

Bolt: $1/2$ " projection

Material thickness: up to $11/16$ "

Barrel diameter: $11/8$ "

Compatibility: Retrofits Best 5L Series

Finish: 626

Rim latch



CL725G

Interchangeable Core format:

CL725G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc cylinder housing, stamped steel back plate and steel case

Material thickness: up to $11/16$ "

Barrel diameter: $11/8$ "

Compatibility: Retrofits Best 5L Series

Finish: 626

Cam locks



CL920R

Interchangeable Core formats:

CL920R - Full Size IC (FSIC)
CL720G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc

Body diameter: $11/8$ "; across flats $7/8$ "

Mounting cutout: $15/32$ "

Material thickness: .08" to $11/8$ "

Finish: 626

Ratchet locks



CL729G

Interchangeable Core formats:

CL929R - Full Size IC (FSIC)
CL729G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc

Body diameter: $11/8$ "

Material thickness: up to $1/4$ "

Finish: 626

Mailbox lock



CL728G

Interchangeable Core format:

CL728G - Small Format IC (SFIC)

Rekeying: Interchangeable core replaced using control key

Body: Die cast zinc housing; steel body

Barrel length: Adjustable

Handing: RH standard

Retrofits: Best BL

Finish: 626

Keying options

Large format keying:

Conventional and FSIC cylinder formats available in standard pin and tumbler, Primus XP and Primus XP UL 437 high-security mechanisms. Everest 29 S123 keyway standard. Classic and restricted keyways also available.

Small format keying:

SFIC cylinder format available in standard pin and tumbler mechanism (A2 pinning); Everest 29 R keyway.

Available keyed alike (KA), keyed different (KD) and master keyed.

FSIC and SFIC construction cores available.

Finishes

Bright brass 605

Satin chrome 626

