CM-221 Series ValueWave™ Touchless Switches







Camden CM-221 Series ValueWave™ switches eliminate the spread of germs through the convenience of hands-free activation, and provides industry-leading dependability and performance.

Ideal for indoor or outdoor use, as part of an automatic door or access control system, ValueWave™ no-touch switches are designed for easy installation and trouble-free service in high traffic applications.

CM-221 Series switches are available in a range of models with narrow, single and double gang stainless steel faceplates and a selection of faceplate graphics.



Features


- Adjustable sensor range 2" to 8" (5 to 20 cm)
- Adjustable time delay (0.5 to 20 sec.) and toggle operation
- Red/green light ring with switch or remote activation
- Weather/water resistant, IP 65 rated
- Single, narrow and double gang stainless steel faceplates
- Selection of faceplate laser etched graphics, resistant to cleaners
- (1) Form 'C' contact, 1A @ 30 VDC

SPECIFICATIONS

SWIT	СН	עום	ISIC	סאר
2001	СП		1310	SINS

	• 12 - 24 VDC ± 10% • FILTERED, REGULATED DC POWER SUPPLY REQUIRED • CONNECTION OF AC VOLTAGE OR DC VOLTAGE ABOVE SPECIFIED RANGE WILL VOID PRODUCT WARRANTY
CURRENT DRAW:	45 mA (PEAK)
RESPONSE TIME:	10ms
TEMPERATURE RANGE:	14°F TO 122°F (-10°C TO +50°C)
CONTACT RATING:	1 AMP @ 30 VDC
CONTACTS:	COMMON / N.O. / N.C.

MODELS					
CM-221/A42	ValueWave™ Touchless Switch, Single Gang, ' Wave to Open ' Graphics. Compatible Surface Mounting Box CM-34BL.				
CM-221/A42N	ValueWave™ Touchless Switch, Narrow (Jamb), ' Wave to Open ' Graphics. Compatible Surface Mounting Box CM-23D				
CM-221/A42W	ValueWave™ Touchless Switch, Double Gang, ' Wave to Open ' Graphics. Compatible Surface Mounting Box CM-53				
CM-221/46	ValueWave™ Touchless Switch, Single Gang, ' Wave to Exit ' Graphics. Compatible Surface Mounting Box CM-34BL				
CM-221/46N	ValueWave™ Touchless Switch, Narrow (Jamb), ' Wave to Exit ' Graphics. Compatible Surface Mounting Box CM-23D				
CM-221/46W	NValueWave™ Touchless Switch, Double Gang, 'Wave to Exit' Graphics. Compatible Surface Mounting Box CM-53				
SWITCH AND POWER SUPPLY KIT					
- P3	Add '- P3' to CM-221 Series Touchless Switch model # for a CX-PS13v3 Linear Power Supply. Provides filtered regulated 12/24V AC/DC Power.				





5502 Timberlea Blvd. Mississauga, ON Canada L4W 2T7 • Toll Free: 1 877 226-3369 (CAMDEN9) Tel: (905) 366-3377 • Fax: (905) 366-3378 • E-mail: info@camdencontrols.com • www.camdencontrols.com

