

HP3000 Series Tubular Lock with Push/Pull Paddle Trim


Strikes

ANSI Curved Lip

(Standard)

Brass, bronze or stainless steel, 4-7/8" (124mm) x 1-1/4" (57mm) x 1-1/4" (57mm) lip to center.

To order with push/pull paddle trim, see Quick Codes, page 6. To order separately, specify 217L13 x Finish.




Full Lip Strike (SF114)

Brass, 2-1/4" x 1-3/4" x 1-1/4" lip to center. No optional lip lengths.

To order separately specify 680L50M020 x Finish.
Anti-rattle tab.

Square Corners




Curved Lip Box

(Optional)

Brass, 2-3/4" (70mm) x 1-1/8" (29mm) x 1-1/4" (57mm) lip to center.

To order with push/pull paddle trim, see Quick Codes, page 6. To order separately, specify 586L19 x Finish.




Full Lip Strike – 1/4" Radius Corners (SFR114)

Brass, 2-1/4" x 1-3/4" x 1-1/4" lip to center. No optional lip lengths.

To order separately specify 680L51M020 x Finish.
Anti-rattle tab.

1/4" Radius Corners



ANSI Wrought Strike Box

To order with push/pull paddle trim, see Quick Codes, page 6.


To order separately, specify 120F76.



Kits


Kit for Retrofitting HP3000 Push/Pull Paddle Trim

Use to cover prep from HL10 series push/pull trim and other manufacturer's trim, when retrofitting HP3000 trim. Contains 2 retrofit plates and 8 screws. Available in 630 finish only. To order, specify 791F39.



Positive Pull Stop Kit

Used on openings where weather stripping is installed or when door closers are not utilized, this kit prevents the latch from retracting when pulling door closed. Contains 2 wood screws, 2 machine screws and instructions. To order, specify 813F068.



Strikes/Kits

ML2000 and ML20900 Mortise Locks with Push/Pull Paddle Trim (HPSK)

Strikes

ANSI Straight Lip (standard)

Brass, bronze or stainless steel

Non-handed

4-7/8" (124mm) x 1-1/4" (32mm) x 1-1/8" (29mm) lip to center (standard)

Optional lip lengths: 7/8" (22mm), 1" (25mm), 1-1/8" (29mm), 1-1/4" (32mm), 1-3/8" (35mm), 1-1/2" (38mm), 1-3/4" (44mm), 2" (51mm), 2-1/4" (57mm), 2-1/2" (64mm), 2-3/4" (70mm), 3" (76mm)

ANSI Curved Lip

Brass, bronze or stainless steel

Handed

4-7/8" (124mm) x 1-1/4" (32mm) x 1-1/4" (32mm) lip to center (standard)


Optional lip lengths: 1-1/8" (29mm), 1-3/8" (35mm), 1-1/2" (38mm), 1-3/4" (44mm), 2" (51mm), 2-1/4" (57mm), 2-1/2" (64mm), 2-3/4" (70mm), 3" (76mm)

ANSI Wrought Strike Box

To order with lockset, see

Quick Codes, page 15.


To order separately, specify 120F76.




Open Back

Size: 5-1/4" (133mm) x 1/4" (32mm).

Note: Only Available with ML2000



Latchbolt x Deadbolt



Latchbolt Only



Deadbolt Only



Blank Filler Plate

Part No.	Description
236L72	Straight Lip
340L60	Curved Lip for RH/LHR
340L61	Curved Lip for LH/RHR
236L73	Straight Lip
340L62	Curved Lip for RH/LHR
340L63	Curved Lip for LH/RHR
236L74	Straight Lip
236L70	Straight Lip


To order strike with lockset, see How to Order, page 15.

To order strike separately, specify Part No. x Lip Length x Finish (e.g., 340L60 x 1-1/2" x 626).

Kits


Positive Pull Stop Kit

Used on openings where weather stripping is installed or when door closers are not utilized, this kit prevents the latch from retracting when pulling door closed. Contains 2 wood screws, 2 machine screws and instructions. To order, specify 813F068.



Hand	Door Thickness	Part
LHR	1-3/4" (44mm)	411L63 016
	2" (51mm)	411L63 018
	2-1/4" (57mm)	411L63 020
RHR	1-3/4" (44mm)	411L62 016
	2" (51mm)	411L62 018
	2-1/4" (57mm)	411L62 020

To order with lockset, see Quick Codes, page 15. To order separately, specify Part No. x Door Thickness x Finish (e.g., 411L62 x 2" x 626).



Rabbeted Front and Strike

Brass or bronze

For 1/2" (13mm) rabbet

No optional lip lengths

	Part No.	Hand
Latchbolt x Deadbolt	318F66	RH/LHR
	318F69	LH/RHR
Latchbolt only	318F64	RH/LHR
	318F67	LH/RHR
Deadbolt only	318F65	RH/LHR
	318F68	LH/RHR

To order with lockset, see Quick Codes, page 15.

To order separately, specify Part No. x Finish (e.g., 318F66 x 626).

