



# Padlocks & Deadlocks

# Product Catalog

Experience a safer  
and more open world

# Deadlocks DL3000 Series

## Padlocks & Deadlocks

### Features



#### Handing

Non-handed, except DL3017, which is handed and field reversible.

#### Door Thickness

Standard: 1-3/4" (44mm) - 2-1/4" (57mm).  
Optional door thicknesses available; see Quick Codes.

#### Backset

Standard: 2-3/4" (70mm)  
Optional: 2-3/8" (60mm)

#### Front

Standard: wrought brass or bronze,  
2-1/4" (57mm) x 1-1/8" (29mm).  
Accommodates flat doors and doors  
beveled 1/8" (3mm) in 2" (51mm).

#### Deadbolt

Zinc diecast hardened steel insert. 1"  
(25mm) throw, 5/8" (16mm) wide x 3/4"  
(19mm) high.

#### Strike

Standard; 2-3/4" (70mm) x 1-1/8"  
(29mm).  
Optional strikes and wrought boxes  
available; see Strikes, this page.

#### Cylinder

Brass, 6-pin, L4 keyway, 0-bitted. Security  
cylinders optional; see Quick Codes.

#### Keys

Two nickel silver standard.

#### Keying Features Available

Master keying  
Construction master keying  
7-pin (FC) conventional  
Interchangeable core (IC)  
Security  
Security (IC)  
Visual key control  
Concealed key control  
Pyramid (FC)  
Pyramid (IC)

#### Warranty

One-year limited.

### Functions


| Outside | Inside | Series/<br>Function | Type                 | ANSI No.        | Function Description  |
|---------|--------|---------------------|----------------------|-----------------|---|
|         |        | DL3013              | Single<br>Cylinder   | E0150<br>Series | - By key outside and by<br>thumbturn inside.  |
|         |        | DL3012              | Double<br>Cylinder   | E0140<br>Series | - By key either side.   |
|         |        | DL3017              | Classroom            | E0170<br>Series | - By key outside and by<br>thumbturn inside.<br>- Thumbturn will retract but not<br>project deadbolt. |
|         |        | DL3011              | Cylinder<br>x Blank  | E0160<br>Series | - By key one side only; opposite<br>side blank.   |
|         |        | DL3060              | Thumbturn<br>x Blank | E0190<br>Series | - By thumbturn one side; opposite<br>side blank.  |

### Strikes




#### Standard Strike

2-3/4" (70mm) x  
1-1/8" (29mm).  
To order separately,  
specify 424F83 x  
Finish.




#### ANSI Strike

Optional; see Quick  
Codes.  
To order separately,  
specify 423L71 x  
Finish.



#### Wrought Strike Box

Standard with  
Standard Strike.  
To order separately,  
specify 496F71-8.




#### ANSI Wrought Strike Box

Optional for use  
with ANSI Strike; see  
Quick Codes.  
To order separately,  
specify 120F76-8.



#### Optional Strike

3-1/2" (89mm) x  
1-1/8" (29mm); see  
Quick Codes.  
To order separately,  
specify 394F19 x  
Finish.



#### Optional Thumbturn

Large profile and  
offset center  
thumbturn makes  
it easier to grasp  
and rotate. To order  
specify Quick Code  
M34. Available for  
DL3013, DL3017,  
DL3060.

**Note:** Interchangeable core not available with 1-3/8" door thickness (D138) option and 2-3/8" backset (B238) option.

# Deadlocks DL3000 Series

## Padlocks & Deadlocks

### Ordering Examples

#### Stock Order

| Quantity | Series/Function | Finish |
|----------|-----------------|--------|
| 24       | DL3013          | 626    |

#### Contract / Detailed Order

| Quantity | Keyset | Series/Function | Finish | Optional Strike | Door Thickness | Misc. Options |
|----------|--------|-----------------|--------|-----------------|----------------|---------------|
| 24       | AA1    | DL3013          | 613    | SS118           | D214           | C6-M17        |

### Quick Codes

#### Finish

|        | Description                             | Specify |
|--------|---|---------|
| US3    | Bright Brass                            | 605     |
| US4    | Satin Brass                             | 606     |
| US10   | Satin Bronze                            | 612     |
| US10B  | Dark Oxidized Satin Bronze, oil rubbed  | 613     |
| US10BE | Dark Oxidized Satin Bronze - equivalent | 613E    |
| US26   | Bright Chromium Plated                  | 625     |
| US26D  | Satin Chromium Plated                   | 626     |
| —      | Black Suede Powder Coat                 | BSP     |
| —      | White Suede Powder Coat                 | WSP     |

#### Strike

| Lip to Center                 | ANSI Straight Lip Specify |
|-------------------------------|---------------------------|
| 7/8" (22mm)                   | SS078                     |
| 1-1/8" (29mm)                 | SS118                     |
| 1-1/4" (32mm)                 | SS114                     |
| 1-3/8" (35mm)                 | SS138                     |
| 1-1/2" (38mm)                 | SS112                     |
| 1-3/4" (44mm)                 | SS134                     |
| 2" (51mm)                     | SS200                     |
| 2-1/4" (57mm)                 | SS214                     |
| 2-1/2" (64mm)                 | SS212                     |
| 2-3/4" (70mm)                 | SS234                     |
| 3" (76mm)                     | SS300                     |
| Other Strikes (no lip)        | Specify                   |
| 2-3/4" (70mm) x 1-1/8" (29mm) | (standard)                |
| 3-1/2" (89mm) x 1-1/8" (29mm) | SD001                     |

#### Door Thickness


| Description               | Specify    |
|---------------------------|------------|
| 1-3/4" (44mm) - 2" (51mm) | (standard) |
| 2-1/4" (57mm)             | D214       |
| 1-3/8" (35mm)             | D138       |

#### Miscellaneous Options

| Description                     | Specify    |
|---------------------------------|------------|
| ANSI wrought strike box         | M17        |
| Ergonomic Thumbturn             | M34        |
| Wrought box for standard strike | (standard) |

#### Cylinder and Keying

| Description   | Specify      |
|---|--------------|
| Conventional 6-pin  | (standard)   |
| Less cylinder(s)  | LC           |
| Interchangeable core (IC) 6-pin                                       | C6           |
| IC 6-pin less core  | CL6          |
| SFIC 6-pin with Less Core   | CLS6         |
| IC 6-pin with temporary construction core                             |              |
| Red   | CT6R         |
| Blue  | CT6B         |
| Green   | CT6G         |
| Conventional 7-pin  | 7P           |
| IC 7-pin  | C7           |
| IC 7-pin with temporary construction core                             |              |
| Red   | CT7R         |
| Blue  | CT7B         |
| Green   | CT7G         |
| IC 7-pin less core  | CL7          |
| SFIC 7-pin with Less Core   | CLS7         |
| Security  | HS           |
| Security IC   | CHS          |
| Pyramid High Security Fixed Core                                      | PHS          |
| Pyramid High Security IC  | PCHS         |
| Pyramid Security Fixed Core   | PS           |
| Pyramid Security IC   | PCS          |
| Pyramid Temp Core   | CTP          |
| Access 3® Patented Fixed Core   | AP           |
| Access 3® Security Fixed Core   | AS           |
| Access 3® High Security Fixed Core                                    | AHS          |
| Access 3® Patented IC   | ACP          |
| Access 3® Security IC   | ACS          |
| Access 3® High Security IC  | ACHS         |
| 0-bitted with 2 blank keys  | (standard)   |
| Keyed random  | KR           |
| Construction master keyed   | CMK          |
| Visual key control (VKC)  |              |
| - Keys only   | VKC1         |
| - Cylinders and keys (not available with HS or CHS)                   | VKC2         |
| - Cylinders only (not available with HS or CHS)                       | VKC3         |
| Concealed key control (CKC)   |              |
| - CKC cylinders and VKC keys  | CKC2         |
| - CKC cylinders only  | CKC3         |
| UL IC 6-Pin Housing Less Core   | CL6AH        |
| UL IC 6-Pin Housing with Disposable Core                              | CTAHD        |
| UL IC 6-Pin Housing with (Red/Blue/Green) Temporary Construction Core | CT6AH(R/B/G) |
| 2 keys per lock   | (standard)   |
| More than 2 keys (e.g., KY6)  | KY#          |



#### Bolt and Front

| Description                             | Part No. | Specify    |
|---|----------|------------|
| 2-3/4" (70mm) backset bolt (less front) | 467F35-8 | (standard) |
| 2-3/8" (60mm) backset bolt (less front) | 693F20-8 | B238       |
| 1-1/8" (29mm) front                     | 467F36   | —          |



#### Cylinder Only

Specify Part No. x Keyway x Finish

| Description                                 | Number         |
|---|----------------|
| Conventional 6-pin                          | 1000-118-A03   |
| Conventional 7-pin                          | 1000-114-A03-7 |
| IC 6-pin                                    | 1080-114-A03   |
| IC 6-pin less core                          | 1070-114-A03   |
| IC 7-pin                                    | 1080-114-A03-7 |
| IC 7-pin less core                          | 1070-114-A03-7 |
| Security                                    | 1010-118-A03   |
| Security IC                                 | 1090-114-A03   |
| Pyramid (FC) Conventional                   | 1020-114-A03   |
| Pyramid (IC)                                | 1030-114-A03   |
| Access 3 Patented Fixed Core                | 1500-114-A03   |
| Access 3 Security Fixed Core                | 1600-114-A03   |
| Access 3 High Security Fixed Core           | 1700-114-A03   |
| Access 3 Patented Interchangeable Core      | 1580-114-A03   |
| Access 3 Security Interchangeable Core      | 1680-114-A03   |
| Access 3 High Security Interchangeable Core | 1788-114-A03   |
| Access 3 UL 6-Pin Housing                   | 1078-114-A03   |