

SoloPlus™ Access Control Management Software

Profile Series v.G1.5



SoloPlus Access Control Management System

The ASSA ABLOY SoloPlus Access Control Management Software allows simple programming and interrogation of the Profile Series v.G1.5 access control products. This software provides the means for fast, convenient assignment of access levels, doors, users, time zones and management of multiple doors with full audit trail capability. Communication between the computer and lock controller is accomplished using either a Data Transfer Device (DTD) or compatible PDA, and allows quick and efficient program transfer and audit trail retrieval.

SoloPlus Features



- Password protected
 - Supports 2,000 users per lock
 - 20,000 user name database
 - 2,000 event transaction history – audit trail to include user entry, date, time, user number, access denied, passage on, passage off, auto unlock, time zone denied, print, audit trail release, program mode, program mode denied, etc.
 - Master code entry at keypad or presentation of “Master” or “CommEnable” proximity credential at lock initiates PC download programming
 - User friendly help feature
 - Extensive report generating feature
 - Directly supports 26, 34, 35 Corporate 1000, and 37 (no site code) bit HID 125 kHz formats or all formats up to 40 bit through use of the enrollment station (ES-G1)
 - Designed for operation with Personal Digital Assistant (PDA) running Palm OS® or DTD
 - PDA/DTD provides convenient, infrared means of transferring information to and from lock using SoloPlus software
 - Capable of up/down loading door information for up to 250 doors when using DTD. Door capacity for a PDA is determined by the available internal memory of the PDA.
 - Access the database(s) from multiple PC locations
 - Auto Backup prompts
 - “User-Friendly” System Setup Task List Guide
 - Enable/Disable/Retire user capability
 - Auto Unlock with or without “first in” authorization
 - First-in Auto-Unlock by specified users*
 - User name import from an external database
 - Forced/Propped Door log events - harness required (option)
- *v.G1.5 controller also required

DTD Data Transfer Device



- Use to download audit trails from v.G1.5 or LK to PC
- Includes SoloPlus™ software

System Requirements

- Data Transfer Device (DTD) or Personal Digital Assistant (PDA)* - See chart for compatible PDA models
- USB Port
- Operating System:
Windows XP (Home, Professional)
Windows Vista (Home Premium, Business)
Windows 7 (Home Premium, Professional)
Windows Server (2003, 2008)
- VGA monitor
- CD ROM drive
- Instruction Manual included on CD

*DTD required for Windows Vista and later.

Compatible PDAs

PDA Manufacturer	Model Number
Aceeca	Meazura
Handspring	Visor
Kyocera	7135 Smart Phone
Palm	IIIc, IIIx, IIIxe, m105, m125, m130, m500, m505, 515, V, Vx, VIIx, Tungsten C, Tungsten E, Tungsten E2, Tungsten T, Tungsten W, TX, Zire, Zire 21, Zire 31, Zire 71, Zire 72
Sony	Clie SJ20

Consult factory for other compatible models.