

# Rim Exit Features

## ED3000 Series



## ED3200 Series      Panic Listed Rim Exit Device

## ED3200A Series      3-Hour Fire Listed Rim Exit Device

### Features

#### Handing

Field reversible (ED3200 Series only); specify hand.

#### Bar Length

Easily field cut to size.

Standard: 36" (914mm) bar fits up to 36" (914mm) door.

Optional: 48" (1219mm) bar fits up to 48" (1219mm) door; specify W048.

#### Door Thickness

1-3/4" (44mm) standard.

Optional: 2" (51mm); specify D200.

Optional: 2-1/4" (57mm); specify D214.

#### Stile

Minimum width 4-1/8" (105mm).

#### Latchbolt

3/4" (19mm) pivoted.

#### Materials

Brass, bronze or stainless steel.

#### Cases

Heavy wrought, 8-3/8" (213mm) x 2-5/8" (67mm).

#### Projection

4-1/2" (114mm); 2-3/4" (70mm) depressed.

#### Crossbar

Standard: round seamless tubing.

Optional: reinforced crossbar; see Quick Codes, page 20.

#### Dogging

Standard on ED3200 Series devices.

Dogging not available on ED3200A Series devices.

#### Fasteners

Standard: machine and wood screws.

Optional: sex nuts and bolts or spanner head screws; see Quick Codes, page 20.

#### Strike

See Options and Accessories, page 14.

#### Removable Mullion

See Mullions, page 16.

#### Cylinders

Cylinder not included unless specified. See How to Order, page 19.

#### Applications and Listings

See page 3.

#### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.3, Grade 1.

Meets A117.1 Accessibility Code.

#### C-UL US

All devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. 3-hour fire-rated devices listed as fire exit hardware for use on 4' x 8' single doors and 8' x 8' double doors. UL symbol on active case cover indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

#### California State Reference Code

This product has been approved by the California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.

#### NFPA

All exit devices comply with NFPA 101 Life Safety Code. All fire-rated devices comply with NFPA 80 Fire Doors and Windows.

#### ADA

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.

### Finishes

BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed
613E	Dark Oxidized Satin Bronze - Equivalent
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield®



# Rim Exit Features

## ED3000 Series

### ED3200 and ED3200A Series Rim Exit Devices

