

ED7000 Series

Product Catalog



Experience a safer
and more open world

Options and Accessories

ED7000 Series



Cylinders

L4 keyway standard; specify other keyways.

Collar not included.

To order with Exit Device, see How to Order, page 19.

To order separately, specify Part No. x Keyway x Finish (e.g., 3000-200-7 x L4 x 605).

| Cylinder Type | Part No. | Description |
|--|--------------------|---|
|  <p>Rim</p> | CR3000-200 | 6-pin, horizontal tailpiece |
| | CR3000-200-7 | 7-pin, horizontal tailpiece |
| | CR3010-200 | 6-pin, horizontal tailpiece, high security |
| | CR3070-178 | 6-pin, interchangeable core (IC) less core |
| | CR3070-178-7 | 7-pin, IC less core |
| | CR3080-178 | 6-pin, IC |
| | CR3080-178-7 | 7-pin, IC |
| | CR3090-178 | 6-pin, high security IC |
| | CR3020-200 | Pyramid High Security fixed core |
| | CR3027-200 | Pyramid Security fixed core |
| | CR3030-178 | Pyramid High Security IC |
| | CR3037-178 | Pyramid Security IC |
|  <p>Mortise</p> | CR1000-118-A02 | 6-pin, 1-1/8" straight cam |
| | CR1000-CR114-A02-7 | 7-pin, 1-1/4" straight cam |
| | CR1010-118-A02 | 6-pin, 1-1/8" high security straight cam |
| | CR1070-114-A02 | 6-pin, 1-1/4" IC less core |
| | CR1080-114-A02 | 6-pin, 1-1/4" IC straight cam |
| | CR1090-114-A02 | 6-pin, 1-1/4" IC high security straight cam |
| | CR1000-118-A91 | 6-pin, 1-1/8" (for 02 and 03 trims only) |
| | CR1000-114-A91-7 | 7-pin, 1-1/4" (for 02 and 03 trims only) |
| | CR1000-138-A01 | 6-pin, 1-3/8" |
| | CR1000-138-A01-7 | 7-pin, 1-3/8" |
| | CR1010-138-A01 | 6-pin, 1-3/8" high security |
| | CR1070-138-A01 | 6-pin, 1-3/8" IC less core |
| | CR1080-138-A01 | 6-pin, 1-3/8" IC |
| | CR1090-138-A01 | 6-pin, 1-3/8" IC high security |
| | CR1000-112-A02 | 6-pin, 1-1/2" straight cam (for B4M, C4M and E4M trims only) |
| | CR1000-112-A02-7 | 7-pin, 1-1/2" straight cam (for B4M, C4M and E4M trims only) |
| | CR1010-112-A02 | 6-pin, 1-1/2" high security straight cam (for B4M, C4M and E4M trims only) |
| | CR1080-112-A02 | 6-pin, 1-1/2" IC straight cam (for B4M, C4M and E4M trims only) |
| | CR1080-112-A02-7 | 7-pin, 1-1/2" IC straight cam (for B4M, C4M and E4M trims only) |
| | CR1090-112-A02 | 6-pin, 1-1/2" IC high security straight cam (for B4M, C4M and E4M trims only) |
| | CR1020-114-A02 | Pyramid High Security fixed core |
| | CR1020-112-A02 | Pyramid High Security fixed core |
| | CR1027-114-A02 | Pyramid Security fixed core |
| | CR1027-112-A02 | Pyramid Security fixed core |
| | CR1030-114-A02 | Pyramid High Security IC |
| | CR1030-138-A02 | Pyramid High Security IC |
| | CR1030-112-A02 | Pyramid High Security IC |
| | CR1037-114-A02 | Pyramid Security IC |
| | CR1037-138-A02 | Pyramid Security IC |
| | CR1037-112-A02 | Pyramid Security IC |

How to Order

ED7000 Series

Cylinder and Keying

| Description | Specify |
|---|-----------------|
| Conventional 6-pin | (standard) |
| Conventional 7-pin | 7P |
| Pyramid Security fixed core | PS |
| Pyramid Security IC | PCS |
| Pyramid High Security fixed core | PHS |
| Pyramid High Security IC | PCHS |
| Pyramid IC with temporary construction core | CTP |
| Pyramid IC less core | CLP |
| Less cylinder(s) | LC |
| High security | HS |
| High security interchangeable core (IC) | CHS |
| IC 6-pin | C6 |
| IC 6-pin with temporary construction core (Red) | CT6R |
| IC 6-pin with temporary construction core (Blue) | CT6B |
| IC 6-pin with temporary construction core (Green) | CT6G |
| IC 6-pin with temporary construction core | CT6 |
| IC 6-pin less core | CL6 |
| SFIC 6-pin with SFIC disposable temporary core | CT6SD |
| IC 7-pin (rim only) | C7 |
| IC 7-pin with temporary construction core (Red) | CT7R |
| IC 7-pin with temporary construction core (Blue) | CT7B |
| IC 7-pin with temporary construction core (Green) | CT7G |
| IC 7-pin with temporary construction core | CT7 |
| IC 7-pin less core (rim only) | CL7 |
| SFIC 7-pin with SFIC disposable temporary core | CT7SD |
| SFIC 6- or 7-pin Small Format Disposable Core | CTSD |
| Master ring (ED7400 only) | MR |
| 0-bitted with 2 blank keys | (standard) |
| Keyed random | KR |
| Construction master keyed | CMK |
| Visual key control (VKC) | |
| No keying data stamped on key or cylinder | VKC0 |
| Keys only | VKC1 |
| Cylinders and keys (not for HS or CHS) | VKC2 |
| Cylinders only (not for HS or CHS) | VKC3 |
| Concealed key control (CKC) | |
| CKC cylinders with VKC keys | CKC2 |
| CKC cylinders only | CKC3 |
| 2 keys per lock | (standard) |
| More than 2 keys | KY# (e.g., KY3) |

Finish

| Description | Specify |
|--|---------|
| US3 Bright Brass | 605 |
| US4 Satin Brass | 606 |
| US9 Bright Bronze | 611 |
| US10 Satin Bronze | 612 |
| US10B Dark Oxidized Satin Bronze, oil rubbed | 613 |
| US14 Bright Nickel Plated | 618 |
| US15 Satin Nickel Plated | 619 |
| US26 Bright Chromium Plated | 625 |
| US26D Satin Chromium Plated | 626 |
| — Satin Chrome Plated with MicroShield® | 626C |
| US32 Bright Stainless Steel | 629 |
| US32D Stain Stainless Steel | 630 |
| — Satin Stainless Steel with MicroShield® | 630C |
| — Black oxidized bronze, oil rubbed | 722 |

Miscellaneous Options

| Description | Specify |
|---|---------|
| Spanner head screws | M02 |
| ANSI wrought strike box | M17 |
| Knurling outside and inside (trim and device; not available with M50) | M20 |
| Knurling outside only (trim side) | M21 |
| Knurling inside only (device side; not available with M50) | M22 |
| Abrasive coat outside and inside (trim and device) | M23 |
| Abrasive coat inside only (device side) | M24 |
| Abrasive coat outside only (trim side) | M25 |
| Stainless steel crossbar (not available with M20 or M22) | M50 |
| Less dogging | M51 |
| Steel reinforced crossbar | M53 |
| Sex nuts and bolts (SNBs) (Not available with ED7800(A) devices) | M54 |
| Shim for 2-3/4" backset on doors with 1/2" stop (rim devices only) | M59 |
| Less latch hold-back (ED7200 devices only) | M66 |

How to Order

ED7000 Series

Strikes

| Description | Specify |
|--|------------|
| Rim | |
| Open rim (ED7200 devices) | (standard) |
| Rim | S07 |
| For aluminum frame with blade stop | S08 |
| Mortised adjustable | S04 |
| Vertical Rod | |
| Top (ED7400 devices) | (standard) |
| Surface projecting bottom (ED7400 devices) | (standard) |
| Flush bottom (ED7400 devices only) | S03 |
| Concealed vertical rod | |
| Top (ED7800 devices) | (standard) |
| 3-hour fire-rated top (ED7800A devices) | (standard) |
| Bottom (ED7800 and ED7800A devices) | (standard) |
| Mortise | |
| ANSI strike | (standard) |
| Open back | |
| 1-3/4" door thickness | SB134 |
| 2" door thickness | SB200 |
| 2-1/4" door thickness | SB214 |

Door Width

| Door Width | Specify |
|------------|------------|
| 36" | (standard) |
| 48" | W048 |

Door Height

| Door Height | Specify |
|------------------------------------|------------|
| 7'6" (ED7400 devices) | (standard) |
| 7'2" (ED7400A and ED7800A devices) | (standard) |
| 10'0" (ED7400 devices only) | H1000 |
| 10'8" (ED7800 devices only) | H1008 |

Handing

| Hand | Specify |
|--------------------|---------|
| Right Hand Reverse | RHR |
| Left Hand Reverse | LHR |

Door Thickness

| Door Thickness | Specify |
|--|------------|
| 1-3/4" | (standard) |
| 2" (except ED7401 x lever trim and ED7800) | D200 |
| 2-1/4" (except ED7401 x lever trim and ED7800) | D214 |