

# Auxiliary Locks



**758 & 858 Padlock Features**

- Cylinder easily removed while in the unlocked position for rekeying
- Available in the following single key sections S, R, U, CR and the following keyway families L, R, H, C, A, B, K, N, V
- Easily keyed into SARGENT master keyed systems
- 6 pin cylinder standard
- Shackle locked by dual ball bearings for extra security



**Specifications: 758 & 858 Padlocks**  
**Body-Solid Brass for exterior applications**

Cylinder	Utilizes standard 10 Line cylinder with shorter padlock tail piece, keyed different as standard (cylinder catalog part no. C750-1)
758	Key retaining. Key removable in locked position only
858	Non key retaining. Key can be removed while unlocked and relocked without key
Case	Satin brass. Solid one piece construction 2" x 2-1/4"
Keys	Two keys provided as standard
Shackle Heights	1" Standard, for 2" (specify 758-2 & 858-2), and 4" (specify 758-4 & 858-4) all 11/32" diameter
Shackle Material	Stainless steel shackle standard for 758 and 858 Hardened steel - optional (specify 758HS or 858HS)
Weather Protection Standard	Shackle protected with rubber shields to prevent freezing in the winter
Chain (optional)	Chain 9" long (specify 758C or 858C)

758 & 858 Padlocks options see page 12

**How To Order**

SC-	758	2	HS	C
Options	Padlocks	Shackle Height	Shackle Material	Chain
Cylinder options see page 11-12	758	1" - Std	Hardened Steel - HS	C
	858	2" - 2		
		4" - 4		

**Keso F1 & Keso 856 & 857 Padlocks**

- Available with Keso F1- and Keso; specify F1-82- for Keso F1- specify 82 for std Keso
- Same cylinder security as offered in other Keso Security System locks. Can be masterkeyed with all locks in the system
- Positive deadlocking construction — no springs which can be forced
- Two stainless steel balls lock shackle. Forcing of shackle increases locking action



82-856 Shown

**Specifications: F1-82-856 and F1-82-857**

856	Non key retaining. Key can be removed while unlocked and relocked without key
857	Key Retaining. Key removable in locked position only
Case	Brass
Case Finishes	Satin brass standard
Case Dimensions	2" x 2" x 1-1/8"
Shackle	Stainless Steel standard Hardened steel, Nickel Plated - optional (specify 856HS or 857HS)
Shackle Diameter	11/32"
Shackle Clearance	1" Standard, for 2-1/2" (specify 856-2 & 857-2), and 4" (specify 856-4 & 857-4)
Weather Protection Standard	Shackle protected with rubber shields to prevent freezing in the winter
Chain (optional)	Chain 9" long (specify 856C or 857C)

**How To Order**

F1-82-	856	-2	HS	C
Options	Padlocks	Shackle Height	Shackle Material	Chain
F1-82-	856	1" - Std	Hardened Steel - HS	C
82-	857	2-1/2" - 2		
		4" - 4		

Copyright © 2007-2019, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.

# Cylinder Options by Product Line

## Auxiliary Locks

**SARGENT®**

**ASSA ABLOY**

Cylinder Type	Option	Description	8200 & 4870 Deadbolt	480 Dead Bolt	470 Dead Bolt	758 & 858 Padlocks	856 & 857 Padlocks	1655 Locker Lock	4141-4143 Utility & Cabinet Locks	4152, 4153, 4253 Utility Locks
Large Format Interchangeable Core (Removable Core)	60-	Hardware to accept Permanent LFIC (Removable Core), Disposable plastic Core provided (Permanent Cores Ordered Separately)	Yes	Yes	N/A	Yes	N/A	N/A	N/A	N/A
	63-	6 pin LFIC permanent core provided	Yes	Yes	N/A	Yes	N/A	N/A	N/A	N/A
	64-	Hardware supplied with Keyed LFIC construction core to accept Permanent LFIC Core (ordered Separately)	Yes	Yes	N/A	Yes	N/A	N/A	N/A	N/A
Small Format Interchangeable Cores	70-	Hardware to accept 6 or 7 Pin SFIC Permanent Cores (ordered separately), plastic disposable core provided	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
	72-	Hardware to accept 6 or 7 Pin SFIC supplied with Keyed Construction Core. (Permanent Core Ordered separately)	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
	73-	Hardware supplied with 6 pin SFIC (Includes masterkeying, grand masterkeying)	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
	65-73-	Hardware provided to accept Uncombined 6 pin SFIC (Permanent) Core - (Packed Loose for field keying)	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
	65-73-7P-	Hardware provided to accept Uncombined 7 pin SFIC (Permanent) Core - (Packed Loose for field keying)	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
	73-7P-	Hardware supplied with Small Format 7 Pin Interchangeable Core (Includes masterkeying, grand masterkeying)	Yes	Yes	N/A	N/A	N/A	N/A	N/A	N/A
Keso F1 & Keso	81-	Hardware provided with housings to accept Keso (83) & Keso F1 (F1-83-) removable cores. (Permanent Cores Ordered Separately)	Yes	N/A	N/A	N/A	N/A	N/A	N/A	Std.
	82-	Hardware provided with standard Keso Security Cylinder	Yes	N/A	N/A	N/A	Std	N/A	N/A	N/A
	F1-82-	Hardware provided with standard Keso F1 Security Cylinder (Patented)	Yes	N/A	N/A	N/A	Specify F1-	N/A	N/A	Specify F1-
	83-	Hardware supplied with SARGENT Keso Security Removable Core cylinder	Yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	F1-83-	Hardware supplied with SARGENT Keso F1 Security Removable Core cylinder (Patented)	Yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	84-	Hardware provided with SARGENT Keso Construction Cores (Permanent Removable Cores ordered separately)	Yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bump Resistant	BR-	Bump Resistant Cylinder (Available with Conventional & Conventional XC Cylinders Only)	Yes	Yes	Yes	Yes	N/A	N/A	N/A	N/A
Less Cylinder	LC-	Less Cylinder	Yes	Yes	Yes	N/A	N/A	N/A	N/A	N/A
Schlage Keyways	SC-	Schlage C keyway cylinder, 0 bitted	Yes	Yes	Yes	Yes	N/A	N/A	N/A	N/A
	SE-	Schlage E keyway cylinder, 0 bitted	Yes	Yes	Yes	Yes	N/A	N/A	N/A	N/A

**NOTE:** For V-10 Cylinder and information, contact ASSA

**NOTE:** When tying into existing key systems contact Key Records for compatibility

+ For use in SARGENT hardware ordered to accept XC- option

Copyright © 2007-2019, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.