



6200 Rim

The 6200 is a narrow stile rim exit device compatible with the aesthetics and functional requirements of contemporary doors. The 6200 comes in varied finishes and can be combined with a variety of trims to match any desired style.

FEATURES

- Designed for narrow stile doors
- 3/4" throw deadlocking stainless steel pullman latch
- Non-handed for easy installation



APPLICATIONS

- Single swing narrow stile doors
- Pairs of narrow stile doors with removable mullions
- Metal and aluminum doors
- 6200 for panic-rated doors only

SPECIFICATIONS

Rail Sizes: -24 for 24" (60cm) doors
 -36 for 30" - 36" (76cm - 91cm) doors
 -42 for 36" - 42" (91cm - 107cm) doors
 -48 for 42" - 48" (107cm - 122cm) doors
 Alternate sizes can be special ordered. Consult Technical Product Support.

Door Thickness: 1-3/4" (44mm) standard. 2" and 2-1/4" (51mm and 57mm) optional, specify when ordering.

Minimum Stile Width: 2" (51mm)

Projection: 3-1/4" (83mm) active; 2-1/2" (63.5mm) dogged

Latchbolt: Stainless steel pullman style, 3/4" (19mm), deadlocking

Strike(s): 759 standard; 793 optional for pairs, panic only

Fasteners: Machine screws or wood door screws standard for panic

Handing: Non-handed

ANSI/BHMA: Certified ANSI/BHMA A156.3 Type 4 Grade 1 standards

Dogging: Hex key dogging standard on panic; optional cylinder dogging (-5)

Shim Kit: #623NS and #625AP optional

Finishes: See page 6 for finish options

Options: Double cylinder function (-2)

