

Experience a safer
and more open world

					
	Mobile credentials	Key fob with Seos®	Key card with Seos®	Key card with Seos® and custom graphics	Key card with Seos® and Prox
Part Number		NTX600-ACCFOB-8K	NTX600-ACCCRD-8K	NTX600-CUSCRD-8K	NTX600-ACCPRX-8K
Technology					
Seos Offline	X	X	X	X	X
Seos Online PACS		X	X	X	X
Prox					X
Dimensions	1.25" x 1.56" x .24" (3.175 x 3.96 x .6 cm)		2.127" x 3.375" x 0.033" max (5.40 x 8.57 x 0.084 cm)		
Online Formatting	Online PACS Format: U100018, 56 Bit, Site code 20				
Operating Frequency	2.4 GHz	13.56 MHz with ISO/IEC 14443 Type A			
Construction	Composite with 60% PVC / 40% PET				
Operating Temperature	-40° to 158° F (-40° to 70° C)				
Weight	0.20 oz (5.5g)				
Memory Size/Application Areas	iCLASS Seos 8K secure processor				
Privacy Mode	Privacy-preserving mode (with encryption of device identifiers)				
Secure Messaging	EN 14890-1 and 7816 aligned using AES algorithm				
Mutual Authentication Mechanism	Based on ISO/IEC 24727-3 2008 with NIST SP800-56A (for session key derivation)				
Write Endurance	Minimum 500,000 cycles				
Contact Smart Chip Embeddable	Yes				
Printable	Yes, for cards only (white/white card)				
	Usable with direct imaging and thermal transfer printers (from HID or other suppliers)				
	Exclusion areas for printing may apply in some areas of the card plastic				
Warranty	Lifetime, see complete warranty policy for details				
Connection Methods	iOS: BLE, Android: NFC and BLE				