BFBarrier-free Exit Devices





Smart design is operating under pressure.

Available option for applications requiring easier operation.

dormakaba continues to meet the evolving needs of our customers. The new BF barrier-free exit device provides a UL/CUL certified solution to meet ADA Standards and California Department of State Architect requirements for maximum 5 lb operating force and conforms to standard UL10C 3 hour fire rating.

Barrier Free Exit Devices

Public Accessibility

dormakaba BF exit hardware meets the needs of openings requiring 5 lb maximum operating force.

 UL/CUL listed under their continuing reinspection programs and conforms to standard UL10C 3hour rated positive pressure testing.



- Complies with NFPA 101 life safety code.
- · Available in architectural finishes
- Limited warranty

Trust dormakaba to meet life safety and compliance challenges with opening solutions that make access in life – smart and secure.



ANSI Exit Device Type	dormakaba Exit Device Model	Functions	Electric Options	Device Lengths	Ratings
Type 1 - Rim	8300BF	01, 02, 03, 05, 08, 23	ES, BPA, BPAR, LM, MS, LM/MS	36" & 48"	Panic & Fire
	9300BF		ES, ESB, BPA, BPAR, LM, MS, LM/MS, LM/MS/BP		
Type 3 - Mortise	9500BF				
Type 4 - Narrow Rim	9700BF				